查询BT137X-600D供应商

Triacs logic level

BT137X series D

GENERAL DESCRIPTION

Glass passivated, sensitive gate triacs in a full pack plastic envelope, intended for use in general purpose bidirectional switching and phase control applications. These devices are intended to be interfaced directly to microcontrollers, logic integrated circuits and other low power gate trigger circuits.

QUICK REFERENCE DATA

SYMBOL	PARAMETER	MAX.	MAX.	UNIT
		BT137X-	**500D**	**600D**	
V_{DRM}	Repetitive peak off-state voltages	500	600	V
$I_{T(RMS)}$	RMS on-state current	8	8	A
I_{TSM}	Non-repetitive peak on-state current	65	65	A

PINNING - SOT186A

PIN	DESCRIPTION
1	main terminal 1
2	main terminal 2
3	gate
case	isolated

PIN CONFIGURATION



SYMBOL



LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.		UNIT
				-500	**-600**	
V_{DRM}	Repetitive peak off-state voltages		-	500[1]	600[1]	V
$I_{T(RMS)}$	RMS on-state current	full sine wave; $T_{hs} \leq 73$ ˚C	-	8		A
I_{TSM}	Non-repetitive peak on-state current	full sine wave; $T_j = 25$ ˚C prior to surge				
		t = 20 ms	-	65		A
		t = 16.7 ms	-	71		A
I^2t	I^2t for fusing	t = 10 ms	-	21		A^2s
dI_T/dt	Repetitive rate of rise of on-state current after triggering	I_{TM} = 12 A; I_G = 0.2 A; dI_G/dt = 0.2 A/µs				
		T2+ G+	-	50		A/µs
		T2+ G-	-	50		A/µs
		T2- G-	-	50		A/µs
		T2- G+	-	10		A/µs
I_{GM}	Peak gate current		-	2		A
V_{GM}	Peak gate voltage		-	5		V
P_{GM}	Peak gate power		-	5		W
$P_{G(AV)}$	Average gate power	over any 20 ms period	-	0.5		W
T_{stg}	Storage temperature		-40	150		˚C
T_j	Operating junction temperature		-	125		˚C

1 Although not recommended, off-state voltages up to 800V may be applied without damage, but the triac may switch to the on-state. The rate of rise of current should not exceed 6 A/µs.

ISOLATION LIMITING VALUE & CHARACTERISTIC

T_{hs} = 25 ˚C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_{isol}	R.M.S. isolation voltage from all three terminals to external heatsink	f = 50-60 Hz; sinusoidal waveform; R.H. ≤ 65% ; clean and dustfree	-		2500	V
C_{isol}	Capacitance from T2 to external heatsink	f = 1 MHz	-	10	-	pF

THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th\ j\text{-}hs}$	Thermal resistance junction to heatsink	full or half cycle				
		with heatsink compound	-	-	4.5	K/W
		without heatsink compound	-	-	6.5	K/W
$R_{th\ j\text{-}a}$	Thermal resistance junction to ambient	in free air	-	55	-	K/W

STATIC CHARACTERISTICS

T_j = 25 ˚C unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS		MIN.	TYP.	MAX.	UNIT
I_{GT}	Gate trigger current	V_D = 12 V; I_T = 0.1 A					
			T2+ G+	-	2.5	5	mA
			T2+ G-	-	3.5	5	mA
			T2- G-	-	3.5	5	mA
			T2- G+	-	6.5	10	mA
I_L	Latching current	V_D = 12 V; I_{GT} = 0.1 A					
			T2+ G+	-	1.6	15	mA
			T2+ G-	-	8.5	20	mA
			T2- G-	-	1.2	15	mA
			T2- G+	-	2.5	20	mA
I_H	Holding current	V_D = 12 V; I_{GT} = 0.1 A		-	1.5	10	mA
V_T	On-state voltage	I_T = 10 A		-	1.3	1.65	V
V_{GT}	Gate trigger voltage	V_D = 12 V; I_T = 0.1 A		-	0.7	1.5	V
		V_D = 400 V; I_T = 0.1 A; T_j = 125 ˚C		0.25	0.4	-	V
I_D	Off-state leakage current	V_D = $V_{DRM(max)}$; T_j = 125 ˚C		-	0.1	0.5	mA

DYNAMIC CHARACTERISTICS

T_j = 25 ˚C unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
dV_D/dt	Critical rate of rise of off-state voltage	V_{DM} = 67% $V_{DRM(max)}$; T_j = 125 ˚C; exponential waveform; R_{GK} = 1 kΩ	-	5	-	V/µs
t_{gt}	Gate controlled turn-on time	I_{TM} = 12 A; V_D = $V_{DRM(max)}$; I_G = 0.1 A; dI_G/dt = 5 A/µs	-	2	-	µs



Fig.1. Maximum on-state dissipation, P_{tot}, versus rms on-state current, $I_{T(RMS)}$, where α = conduction angle.



Fig.4. Maximum permissible rms current $I_{T(RMS)}$, versus heatsink temperature T_{hs}.



Fig.2. Maximum permissible non-repetitive peak on-state current I_{TSM}, versus pulse width t_p, for sinusoidal currents, $t_p \leq 20ms$.



Fig.5. Maximum permissible repetitive rms on-state current $I_{T(RMS)}$, versus surge duration, for sinusoidal currents, f = 50 Hz; $T_{hs} \leq 73˚C$.



Fig.3. Maximum permissible non-repetitive peak on-state current I_{TSM}, versus number of cycles, for sinusoidal currents, f = 50 Hz.



Fig.6. Normalised gate trigger voltage $V_{GT}(T_j)/ V_{GT}(25˚C)$, versus junction temperature T_j.



Fig.7. Normalised gate trigger current $I_{GT}(T_j)/ I_{GT}(25˚C)$, versus junction temperature T_j.



Fig.10. Typical and maximum on-state characteristic.



Fig.8. Normalised latching current $I_L(T_j)/ I_L(25˚C)$, versus junction temperature T_j.



Fig.11. Transient thermal impedance $Z_{th\ j\text{-}hs}$, versus pulse width t_p.



Fig.9. Normalised holding current $I_H(T_j)/ I_H(25˚C)$, versus junction temperature T_j.



Fig.12. Typical, critical rate of rise of off-state voltage, dV_D/dt versus junction temperature T_j.

MECHANICAL DATA

Dimensions in mm

Net Mass: 2 g



Fig.13. SOT186A; The seating plane is electrically isolated from all terminals.

Notes
1. Refer to mounting instructions for F-pack envelopes.
2. Epoxy meets UL94 V0 at 1/8".

DEFINITIONS

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	
© **Philips Electronics N.V. 1997**	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.